TRUE

400 TREADMILL

The C400 Treadmill provides your commercial facility reliable performance and a high-quality experience with patented features like HRC Heart Rate Control® and TRUE'S low-impact Soft System®. In addition, the C400 is the ideal choice for rehabilitation use at health and medical facilities with a low speed of only .2 mph. A variety of console options provide the technology, features, and asset management needed for your facility.



• Minimum Speed: 0.2 MPH (0.3 KPH)

• Optional medical handrails

• Patented HRC Cruise Control® and Soft System® deck

• Multiple console options available

SPECIFICATIONS

DIMENSIONS (L X W X H)

79" x 31.5" x 62" / 200.66 cm x 80.01 cm x 157.48 cm

SPEED

0.2 to 12.0 MPH / 0.3 to 19 KPH

INCLINE/DECLINE LEVELS

0% to 15%

PRODUCT WEIGHT

349 lbs / 158.3 kg

COLOR

Charcoal/Black



CONSOLE OPTIONS



ENVISION



ENVISION WITH COMPASS



EMERGE



ESCALATE



IGNITE

400 SERIES



C400 TREADMILL

TECHNICAL SPECIFICATIONS	Power Source	120V/20A (NEMA 5-20R receptacle) 230V/15A
	Cord Length	230V/15A (NEMA 6-15R receptacle)
	Drive Motor	TRUE 4HP Max Drive AC motor
	Power Factor Correction (PFC)	Standard
	Incline Motor	1,200 lbs. of thrust
	Speed Sensor	Optical
	Deck	1" / 2.54 cm Medium Density Fiberboard
	Reversible Deck	Standard
	Belt	Lubricant Infused Siegling Multi-Ply with PVC Coating
	Rollers	3" / 8 cm w/ Shielded Bearings
	Impact System	True Soft System®
	Frame Construction	Robotically Welded Heavy-Gauge Steel
	Lubrication	Silax
	Speed Range	0.2 to 12.0 MPH / 0.3 to 19 KPH
_	Incline/Decline Range	0% to 15%
	Quick Access Control	Speed, Incline, Start and Stop on Quick Access Point
	Handrail Design	Extended Handrails with Rubber, Moisture-Resistant Grips
	Contact Heart Rate Monitoring	Yes
	Wireless Heart Rate Monitoring	Polar®
AVAILABLE CONSOLES		Envision ¹⁶ with Comapass, Envision ¹⁸ , Escalate ⁸ , Emerge, Ignite
ASSET TRACKING		EcoFit Compatible
SAFETY	Safety Clip	Removable
	Extended Handrails	Standard
	Large Straddle Covers	Standard
	User Detection	User Present Detection™
REGULATORY APPROVALS		ETL UL1647, CSA, CE, EN957, (ISO 20957), FCC
EXTRAS	Accessories	Water Bottle Holder (2), Accessory Tray, Over Molded Reading Rack/Tablet Holder, Optional Medical Handrails
PHYSICAL SPECIFICATIONS	Footprint	79" L x 31.5" W x 62" H / 200.66 cm x 80.01 cm x 15748 cm
	Running Surface	60" L x 22" W / 1524 cm x 55.88 cm
	Machine Weight	349 lbs / 158.3 kg
	Shipping Weight	424 lbs / 192.3 kg
	Maximum User Weight	400 lbs / 1814 kg
	Step-Up Height	6.5" / 16.51 cm
	Portability	2 Front Transport Wheels
WARRANTY	Warranty Type	Commercial (non-dues paying facilities with less than 8 hours of usage per day)
	Frame	Lifetime
	Motor	5 Years
	Parts	5 Years (Envision ¹⁶ Console is 3 years)
	Labor	2 Years

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.

